

# DR240 Series | DIN Rail Power Supply

## 240W

- 100-240Vac (125-370Vdc) input voltage range
- 35mm DIN rail installation
- High reliability
- Built-in EMI filter
- Short circuit, over current and over voltage protection
- Free air/convection cooled
- 100% burn-in test
- DC power ON indicator
- DC low voltage indicator
- 3-year warranty



## Description

The DR240 Series is a 240W, universal input, single output power supply that uses DIN Rail mounting to simplify installation and maintenance. This series is used in factory automation, process control and functional modules.

## Specifications

### Input

Input Voltage	• 90 - 264 Vac, Min. - Max. 125 - 370 Vdc
Input Frequency	• 47 Hz to 63 Hz
Power Factor	• 0.93 - 0.98, Min. - Max.
Inrush Current	• 50A @ $V_{in} = 115\text{Vac}$ , cold start, full load 50A @ $V_{in} = 230\text{Vac}$ , cold start, full load
Input Current	• 2.5A @ $V_{in} = 115\text{Vac}$ , full load 1.25A @ $V_{in} = 230\text{Vac}$ , full load
Turn-on delay time	• 3.6S Max @ $V_{in} = 115\text{Vac}$ , full load

### Output

Voltage adjustment range	• -10 to +20% $V_{out}$
Line Regulation	• $\pm 1\%$ typical
Load Regulation	• $\pm 1\%$ typical $V_{out}$ from min. to max.
Hold-on time	• 20 ms typ., $V_{in} = 115\text{Vac}$ , full load
Ripple & Noise	• 120mV typical, 150mV maximum
Over current	• Type: 110-150%; Hiccup mode, recovers automatically after fault conditions are removed
Short circuit	• Hiccup mode, recovers automatically after fault conditions are removed
Over voltage	• Type: 110-150%; Hiccup mode, recovers automatically after fault conditions are removed
DC-OK Lamp	• LED (Green)
DC-Low Lamp	• LED (Red)
Parallel/series operation	• Series operation is possible

### Environmental

Storage Temperature	• -40°C to +85°C, 5% to 95% RH
Ambient operating temperature	• -25 to +70°C, startup at rated voltage Derating from 50°C to 70°C : 2.5% / °C
Operating relative humidity	• 20 to 95% RH, non-condensing
MTBF	• 200kHrs Full load, 230Vac input, 25°C ambient temperature
Dimension (WxHxD)	• 60 x 130 x 125mm 2.36 x 5.12 x 4.92 in

### EMC & Safety

Withstand voltage	• Input-output: 3kVac Input-ground: 2kVac Output-ground: 0.5kVac
Safety standards	• UL, C-UL, CE, CB
EMC	• FCC Part 15 Class B, CLSPR22-B, EN55022-B
THD	• EN61000-3-2 (Class-A)

# DR240 Series | DIN Rail Power Supply

## Output Specifications

Model No.	Input voltage (Vac)	Output voltage (Vdc)	Output current (A)	Output Voltage Adjustment	Ripple Noise	Line Reg.	Load Reg.	Efficiency Typ.
DR240-24	100-240	24	10	-10% to +20%	≤150mV	±1%	±1%	90%
DR240-48	100-240	48	5	-10% to +20%	≤150mV	±1%	±1%	92%

### Notes:

1. Rated Load and Rated Input Voltage, Ta=25°C;
2. Ripple & Noise are measured at 20MHZ of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uF parallel capacitor.

## Mechanical Specifications

